



## RAPID Plus Engine & Chassis Cleaner

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

RAPID Plus Engine & Chassis Cleaner

UFI: GNRQ-E1RY-1UDV-8ED1

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

##### Use of the substance/mixture

Washing and cleaning products

#### 1.3. Details of the supplier of the safety data sheet

Company name: SCHOLL Concepts GmbH

Polish & Pad Manufaktur

Street: Maybachstrasse 7

Place: D-71686 Remseck

Telephone: +49 (0) 7141 29299 - 0

Telefax: +49 (0) 7141 29299 - 10

e-mail: sds@schollconcepts.com

Contact person: Labor

Internet: www.schollconcepts.com

#### 1.4. Emergency telephone number:

+49 (0) 89 19240 (Giftnotruf Technische Universität München)

### SECTION 2: Hazards identification

#### 2.1. Classification of the substance or mixture

##### Regulation (EG) Nr. 1272/2008

Skin Corr. 1; H314

Eye Dam. 1; H318

Full text of hazard statements: see SECTION 16.

#### 2.2. Label elements

##### Regulation (EG) Nr. 1272/2008

##### Hazard components for labelling

disodium metasilicate pentahydrate

Octyldecyl Glucoside

Cocamidopropyl betaine

Sodium hydroxide

Signal word: Danger



## RAPID Plus Engine & Chassis Cleaner

### Pictograms:



### Hazard statements

H314 Causes severe skin burns and eye damage.

### Precautionary statements

P102 Keep out of reach of children.  
P260 Do not breathe dust/fume/gas/mist/vapours/spray.  
P264 Wash hands thoroughly after handling.  
P271 Use only outdoors or in a well-ventilated area.  
P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
P315 Get immediate medical advice/attention.  
P302+P352 IF ON SKIN: Wash with plenty of water.  
P332+P313 If skin irritation occurs: Get medical advice/attention.  
P501 Dispose of waste according to applicable legislation.

### 2.3. Other hazards

No information available.

## SECTION 3: Composition/information on ingredients

### 3.2. Mixtures



**RAPID Plus Engine & Chassis Cleaner**

**Hazardous components**

CAS No	Chemical name			Quantity
	EC No	Index No	REACH No	
	Classification (Regulation (EG) Nr. 1272/2008)			
6834-92-0	disodium metasilicate			10 - < 15 %
	229-912-9	014-010-00-8	01-2119449811-37	
	Met. Corr. 1, Skin Corr. 1B, STOT SE 3; H290 H314 H335			
68515-73-1	Octyldecyl Glucoside			10 - < 15 %
	500-220-1		01-2119488530-36	
	Eye Dam. 1; H318			
147170-44-3	Cocamidopropyl betaine			10 - < 15 %
	931-333-8		01-2119489410-39	
	Eye Dam. 1, Aquatic Chronic 3; H318 H412			
64-02-8	tetrasodium ethylene diamine tetraacetate			1 - < 5 %
	200-573-9	607-428-00-2	01-2119486762-27	
	Acute Tox. 4, Eye Dam. 1; H302 H318			
1310-73-2	Sodium hydroxide			< 1 %
	215-185-5		01-2119457892-27	
	Met. Corr. 1, Skin Corr. 1A; H290 H314			

Full text of H and EUH statements: see section 16.

**Specific Conc. Limits, M-factors and ATE**

CAS No	EC No	Chemical name	Quantity
	Specific Conc. Limits, M-factors and ATE		
6834-92-0	229-912-9	disodium metasilicate	10 - < 15 %
	inhalation: LC50 = >2,06 mg/l (vapours); dermal: LD50 = >5000 mg/kg; oral: LD50 = 1372 mg/kg		
68515-73-1	500-220-1	Octyldecyl Glucoside	10 - < 15 %
	dermal: LD50 = >2000 mg/kg; oral: LD50 = >2000 mg/kg		
147170-44-3	931-333-8	Cocamidopropyl betaine	10 - < 15 %
	dermal: LD50 = >2000 mg/kg; oral: LD50 = 2335 mg/kg		
64-02-8	200-573-9	tetrasodium ethylene diamine tetraacetate	1 - < 5 %
	oral: LD50 = 1780-2000 mg/kg		
1310-73-2	215-185-5	Sodium hydroxide	< 1 %
	dermal: LD50 = 1350 mg/kg; oral: LD50 = >191 mg/kg Skin Corr. 1A; H314: >= 5 - 100 Skin Corr. 1B; H314: >= 2 - < 5 Skin Irrit. 2; H315: >= 0,5 - < 2 Eye Irrit. 2; H319: >= 0,5 - < 2		



## RAPID Plus Engine & Chassis Cleaner

### Labelling for contents according to Regulation (EC) No 648/2004

5 % - < 15 % non-ionic surfactants, 5 % - < 15 % amphoteric surfactants, < 5 % EDTA and salts thereof.

## SECTION 4: First aid measures

### 4.1. Description of first aid measures

#### General information

IF exposed or concerned: Call a doctor. When in doubt or if symptoms are observed, get medical advice.  
Remove contaminated, saturated clothing immediately.

#### After inhalation

Provide fresh air. In case of respiratory tract irritation, consult a physician.

#### After contact with skin

After contact with skin, wash immediately with plenty of water and soap. Take off contaminated clothing and wash it before reuse. If skin irritation occurs: Get medical advice/attention.

#### After contact with eyes

After contact with the eyes, rinse with water with the eyelids open for a sufficient length of time, then consult an ophthalmologist immediately.

#### After ingestion

Rinse mouth immediately and drink plenty of water. Do NOT induce vomiting. Call a physician immediately.

### 4.2. Most important symptoms and effects, both acute and delayed

No information available.

### 4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

## SECTION 5: Firefighting measures

### 5.1. Extinguishing media

#### Suitable extinguishing media

Foam. Dry extinguishing powder. Carbon dioxide (CO<sub>2</sub>). Water spray jet. Co-ordinate fire-fighting measures to the fire surroundings.

#### Unsuitable extinguishing media

Full water jet

### 5.2. Special hazards arising from the substance or mixture

In case of fire may be liberated: Gases/vapours, corrosive

### 5.3. Advice for firefighters

Wear a self-contained breathing apparatus and chemical protective clothing. Full protection suit

### Additional information

Use water spray jet to protect personnel and to cool endangered containers. Suppress gases/vapours/mists with water spray jet. Collect contaminated fire extinguishing water separately. Do not allow entering drains or



## RAPID Plus Engine & Chassis Cleaner

surface water.

### SECTION 6: Accidental release measures

#### 6.1. Personal precautions, protective equipment and emergency procedures

##### General advice

Provide adequate ventilation. Do not breathe gas/fumes/vapour/spray. Avoid contact with skin, eyes and clothes. Use personal protection equipment.

##### For non-emergency personnel

Remove all sources of ignition. Remove persons to safety. Ventilate affected area. Wear personal protection equipment (refer to section 8).

##### For emergency responders

Wear breathing apparatus if exposed to vapours/dusts/aerosols. Use personal protection equipment. Material, alkali-resistant

#### 6.2. Environmental precautions

Do not allow to enter into surface water or drains. Do not allow to enter into soil/subsoil.

#### 6.3. Methods and material for containment and cleaning up

##### For containment

Stop leak if safe to do so. Cover drains. Collect spillage. Collect in closed and suitable containers for disposal.

##### For cleaning up

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents). Treat the recovered material as prescribed in the section on waste disposal.

##### Other information

Use non-sparking tools. Clean contaminated articles and floor according to the environmental legislation.

#### 6.4. Reference to other sections

Safe handling: see section 7

Personal protection equipment: see section 8

Disposal: see section 13

### SECTION 7: Handling and storage

#### 7.1. Precautions for safe handling

##### Advice on safe handling

Use only in well-ventilated areas. If handled uncovered, arrangements with local exhaust ventilation have to be used. Do not breathe gas/fumes/vapour/spray. Handle and open container with care.

##### Advice on protection against fire and explosion

No special fire protection measures are necessary. Only use the material in places where open light, fire and other flammable sources can be kept away.

##### Advice on general occupational hygiene

Wear protective gloves/protective clothing. Remove contaminated, saturated clothing immediately. Wash



## RAPID Plus Engine & Chassis Cleaner

hands and face before breaks and after work and take a shower if necessary. When using do not eat or drink. When using do not smoke. Avoid contact with skin, eyes and clothes. Avoid breathing dust/fume/gas/mist/vapours/spray. Draw up and observe skin protection programme.

### 7.2. Conditions for safe storage, including any incompatibilities

#### Requirements for storage rooms and vessels

Keep only in the original container in a cool, well-ventilated place. Keep container tightly closed. Store in a place accessible by authorized persons only. Provide adequate ventilation as well as local exhaust at critical locations.

#### Hints on joint storage

Do not store together with: Oxidising agent. Strong acid. Strong alkali.

#### Further information on storage conditions

Recommended storage temperature: 15-25°C

## SECTION 8: Exposure controls/personal protection

### 8.1. Control parameters

#### Exposure limits (EH40)

CAS No	Substance	ppm	mg/m <sup>3</sup>	fibres/ml	Category	Origin
1310-73-2	Sodium hydroxide	-	2		STEL (15 min)	WEL



## RAPID Plus Engine & Chassis Cleaner

### DNEL/DMEL values

CAS No	Substance	Exposure route	Effect	Value
6834-92-0	disodium metasilicate			
Worker DNEL, long-term		inhalation	systemic	6,22 mg/m <sup>3</sup>
Worker DNEL, long-term		dermal	systemic	1,49 mg/kg bw/day
Consumer DNEL, long-term		inhalation	systemic	1,55 mg/m <sup>3</sup>
Consumer DNEL, long-term		dermal	systemic	0,74 mg/kg bw/day
Consumer DNEL, long-term		oral	systemic	0,74 mg/kg bw/day
68515-73-1	Octyldecyl Glucoside			
Worker DNEL, long-term		dermal	systemic	595000 mg/kg bw/day
Worker DNEL, long-term		inhalation	systemic	420 mg/m <sup>3</sup>
Consumer DNEL, long-term		dermal	systemic	357000 mg/kg bw/day
Consumer DNEL, long-term		oral	systemic	35,7 mg/kg bw/day
Consumer DNEL, long-term		inhalation	systemic	124 mg/m <sup>3</sup>
147170-44-3	Cocamidopropyl betaine			
Worker DNEL, long-term		inhalation	systemic	44 mg/m <sup>3</sup>
Worker DNEL, long-term		dermal	systemic	12,5 mg/kg bw/day
Consumer DNEL, long-term		inhalation	systemic	13,04 mg/m <sup>3</sup>
Consumer DNEL, long-term		dermal	systemic	7,5 mg/kg bw/day
64-02-8	tetrasodium ethylene diamine tetraacetate			
Worker DNEL, long-term		inhalation	local	1,5 mg/m <sup>3</sup>
Worker DNEL, acute		inhalation	local	3 mg/m <sup>3</sup>
Consumer DNEL, long-term		inhalation	local	0,6 mg/m <sup>3</sup>
Consumer DNEL, acute		inhalation	local	1,2 mg/m <sup>3</sup>
Consumer DNEL, long-term		oral	systemic	25 mg/kg bw/day
Worker DNEL, acute		inhalation	systemic	3 mg/m <sup>3</sup>
1310-73-2	Sodium hydroxide			
Worker DNEL, long-term		inhalation	local	1 mg/m <sup>3</sup>

## RAPID Plus Engine & Chassis Cleaner

Consumer DNEL, long-term	inhalation	local	1 mg/m <sup>3</sup>
--------------------------	------------	-------	---------------------

### PNEC values

CAS No	Substance	Value
Environmental compartment		Value
6834-92-0	disodium metasilicate	
Freshwater		7,5 mg/l
Marine water		1 mg/l
68515-73-1	Octyldecyl Glucoside	
Freshwater		0,176 mg/l
Marine water		0,0176 mg/l
Freshwater sediment		1,516 mg/kg
Marine sediment		0,152 mg/kg
Secondary poisoning		111,11 mg/kg
Micro-organisms in sewage treatment plants (STP)		560 mg/l
Soil		0,654 mg/kg
147170-44-3	Cocamidopropyl betaine	
Freshwater		0,013 mg/l
Marine water		0,0013 mg/l
Freshwater sediment		14,8 mg/kg
Marine sediment		1,48 mg/kg
Soil		0,8 mg/kg
64-02-8	tetrasodium ethylene diamine tetraacetate	
Freshwater		2,83 mg/l
Marine water		0,283 mg/l
Micro-organisms in sewage treatment plants (STP)		50 mg/l
Soil		1,1 mg/kg

### 8.2. Exposure controls



#### Appropriate engineering controls

Use only in well-ventilated areas. If handled uncovered, arrangements with local exhaust ventilation have to be used. Do not breathe gas/fumes/vapour/spray.





## RAPID Plus Engine & Chassis Cleaner

### Individual protection measures, such as personal protective equipment

#### Eye/face protection

Wear eye/face protection. Suitable eye protection: Eye glasses with side protection (EN 166)

#### Hand protection

When handling with chemical substances, protective gloves must be worn with the CE-label including the four control digits. The quality of the protective gloves resistant to chemicals must be chosen as a function of the specific working place concentration and quantity of hazardous substances. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

Recommended glove articles : Dermatril P 743, Thickness of the glove material 0,2 mm, level 2 >= 30 min. (DIN EN 374)

#### Skin protection

Wear suitable protective clothing.

#### Respiratory protection

In case of inadequate ventilation wear respiratory protection.

#### Environmental exposure controls

No special environmental measures are necessary. Do not allow uncontrolled discharge of product into the environment.

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

Physical state:	Liquid	
Colour:	blue	
Odour:	characteristic	
Melting point/freezing point:		not determined
Boiling point or initial boiling point and boiling range:		100 °C
Flammability		
Solid/liquid:		not applicable
Gas:		not applicable
Lower explosion limits:		not applicable
Upper explosion limits:		not applicable
Flash point:		not applicable
Auto-ignition temperature:		not applicable
Decomposition temperature:		not determined
pH-Value (at 20 °C):		13
Water solubility:		easily soluble
Solubility in other solvents		
not determined		
Partition coefficient n-octanol/water:		not determined



## RAPID Plus Engine & Chassis Cleaner

Vapour pressure: (at 20 °C)	not applicable
Vapour pressure: (at 50 °C)	not applicable
Relative density (at 20 °C):	1,085
Relative vapour density:	not determined

### 9.2. Other information

#### Information with regard to physical hazard classes

Oxidizing properties  
Not oxidising.

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

No hazardous reaction when handled and stored according to provisions.

### 10.2. Chemical stability

The product is stable under storage at normal ambient temperatures.

### 10.3. Possibility of hazardous reactions

No known hazardous reactions.

### 10.4. Conditions to avoid

Frost

### 10.5. Incompatible materials

Strong acid. Strong alkali. Oxidising agent.

### 10.6. Hazardous decomposition products

No known hazardous decomposition products.

## SECTION 11: Toxicological information

### 11.1. Information on hazard classes as defined in CLP Regulation

#### Toxicokinetics, metabolism and distribution

No information available.

#### Acute toxicity

Based on available data, the classification criteria are not met.



## RAPID Plus Engine & Chassis Cleaner

CAS No	Chemical name				
	Exposure route	Dose	Species	Source	Method
6834-92-0	disodium metasilicate				
	oral	LD50 mg/kg 1372	Mouse	ECHA	
	dermal	LD50 mg/kg >5000	Rat	ECHA	EPA OPPTS 870.1200
	inhalation (4 h) vapour	LC50 mg/l >2,06	Rat	ECHA	EPA OPPTS 870.1300
68515-73-1	Octyldecyl Glucoside				
	oral	LD50 mg/kg >2000	Rat	ECHA	OECD 423
	dermal	LD50 mg/kg >2000	Rabbit	ECHA	OECD 402
147170-44-3	Cocamidopropyl betaine				
	oral	LD50 mg/kg 2335	Rat	ECHA	OECD 401
	dermal	LD50 mg/kg >2000	Rat	ECHA	OECD 402
64-02-8	tetrasodium ethylene diamine tetraacetate				
	oral	LD50 2000 mg/kg 1780-	Rat	ECHA	OECD 401
1310-73-2	Sodium hydroxide				
	oral	LD50 mg/kg >191	Rat		
	dermal	LD50 mg/kg 1350	Rabbit		

### Irritation and corrosivity

Causes severe skin burns and eye damage.

Causes serious eye damage.

### Sensitising effects

Based on available data, the classification criteria are not met.

### Carcinogenic/mutagenic/toxic effects for reproduction

Based on available data, the classification criteria are not met.

### STOT-single exposure

Based on available data, the classification criteria are not met.

### STOT-repeated exposure

Based on available data, the classification criteria are not met.



THE SCIENCE OF GLOSS

Page 12 of 18

Safety Data Sheet According to Regulation (EG) Nr. 1907/2006

Revision date: 22.12.2022/Revision No:2,06

PDF Print date: 22.12.2022

## RAPID Plus Engine & Chassis Cleaner

### Aspiration hazard

Based on available data, the classification criteria are not met.

### Additional information on tests

The mixture is classified as hazardous according to regulation (EC) No 1272/2008 [CLP].

## SECTION 12: Ecological information

### 12.1. Toxicity

Based on available data, the classification criteria are not met.



## RAPID Plus Engine & Chassis Cleaner

CAS No	Chemical name					
	Aquatic toxicity	Dose	[h]   [d]	Species	Source	Method
6834-92-0	disodium metasilicate					
	Acute fish toxicity	LC50 210 mg/l	96 h	Danio rerio (zebrafish)	ECHA	OECD 203
	Acute algae toxicity	ErC50 207 mg/l	72 h	Pseudokirchneriella subcapitata	ECHA	OECD 201
	Acute crustacea toxicity	EC50 1700 mg/l	48 h	Daphnia magna (Big water flea)	ECHA	EU Method C.2
68515-73-1	Octyldecyl Glucoside					
	Acute fish toxicity	LC50 170 mg/l	96 h	Danio rerio (zebrafish)	ECHA	ISO 7346/1-3
	Acute algae toxicity	ErC50 27,22 mg/l	72 h	Scenedesmus subspicatus	ECHA	(DIN 38412, part 9)
	Acute crustacea toxicity	EC50 >100 mg/l	48 h	Daphnia magna (Big water flea)	ECHA	OECD 202
147170-44-3	Cocamidopropyl betaine					
	Acute fish toxicity	LC50 1,1 mg/l	96 h	Danio rerio (zebrafish)	ECHA	OECD 203
	Acute algae toxicity	ErC50 1,5 mg/l	72 h	Pseudokirchneriella subcapitata	ECHA	OECD 201
	Acute crustacea toxicity	EC50 1,9 mg/l	48 h	Daphnia magna (Big water flea)	ECHA	OECD 202
	Fish toxicity	NOEC 1,1 mg/l	4 d	Danio rerio (zebrafish)	ECHA	OECD 203
	Algae toxicity	NOEC 0,3 mg/l	3 d	Pseudokirchneriella subcapitata	ECHA	OECD 201
	Crustacea toxicity	NOEC 7 mg/l	2 d	Daphnia magna (Big water flea)	ECHA	OECD 202
64-02-8	tetrasodium ethylene diamine tetraacetate					
	Acute fish toxicity	LC50 >100 mg/l	96 h	Oncorhynchus mykiss (Rainbow trout)	ECHA	OECD 203
	Acute algae toxicity	ErC50 >100 mg/l	72 h	Pseudokirchneriella subcapitata	ECHA	OECD 201
	Acute crustacea toxicity	EC50 >100 mg/l	48 h	Daphnia magna (Big water flea)	ECHA	DIN 38412, part 11
	Fish toxicity	NOEC >35,1 mg/l	35 d	Danio rerio (zebrafish)	ECHA	OECD 210
	Algae toxicity	NOEC 48,4 mg/l	3 d	Pseudokirchneriella subcapitata	ECHA	OECD 201
1310-73-2	Sodium hydroxide					
	Acute fish toxicity	LC50 45,4 mg/l	96 h	Onchorhynchus mykiss		

**RAPID Plus Engine & Chassis Cleaner**

	Acute crustacea toxicity	EC50 mg/l	30-100	48 h	Saltwater Shrimp	ECHA	
--	--------------------------	--------------	--------	------	------------------	------	--

**12.2. Persistence and degradability**

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

The surfactants contained in this mixture comply with the biodegradability criteria as laid down in Regulation (EC) No.648/2004 on detergents.

CAS No	Chemical name	Method	Value	d	Source
		Evaluation			
68515-73-1	Octyldecyl Glucoside	OECD 301E	100%	28	
		Readily biodegradable (according to OECD criteria).			
147170-44-3	Cocamidopropyl betaine	OECD 301B	91,6%	28	ECHA
		Readily biodegradable (according to OECD criteria).			
64-02-8	tetrasodium ethylene diamine tetraacetate	OECD 301D	2%	28	ECHA
		Poorly biodegradable. Not readily biodegradable (according to OECD criteria)			

**12.3. Bioaccumulative potential**

The product has not been tested.

**BCF**

CAS No	Chemical name	BCF	Species	Source
147170-44-3	Cocamidopropyl betaine	<71		

**12.4. Mobility in soil**

The product has not been tested.

**12.5. Results of PBT and vPvB assessment**

The substances in the mixture do not meet the PBT/vPvB criteria according to UK REACH.

The product has not been tested.

**12.6. Endocrine disrupting properties**

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

**12.7. Other adverse effects**

No information available.

**Further information**

Do not allow to enter into surface water or drains. Do not allow to enter into soil/subsoil.

**SECTION 13: Disposal considerations**

## RAPID Plus Engine & Chassis Cleaner

### 13.1. Waste treatment methods

#### Disposal recommendations

This material and its container must be disposed of as hazardous waste. Do not allow to enter into surface water or drains. Do not allow to enter into soil/subsoil. Dispose of waste according to applicable legislation.

#### Contaminated packaging

Non-contaminated packages may be recycled. Handle contaminated packages in the same way as the substance itself.

## SECTION 14: Transport information

### Land transport (ADR/RID)

14.1. UN number or ID number:	UN 1719
14.2. UN proper shipping name:	CAUSTIC ALKALI LIQUID, N.O.S. (SODIUM HYDROXIDE, SOLID)
14.3. Transport hazard class(es):	8
14.4. Packing group:	III
Hazard label:	8



Classification code:	C5
Special Provisions:	274
Limited quantity:	5 L
Excepted quantity:	E1
Transport category:	3
Hazard No:	80
Tunnel restriction code:	E

### Inland waterways transport (ADN)

14.1. UN number or ID number:	UN 1719
14.2. UN proper shipping name:	CAUSTIC ALKALI LIQUID, N.O.S. (SODIUM HYDROXIDE, SOLID)
14.3. Transport hazard class(es):	8
14.4. Packing group:	III
Hazard label:	8



Classification code:	C5
Special Provisions:	274
Limited quantity:	5 L
Excepted quantity:	E1

### Marine transport (IMDG)

**RAPID Plus Engine & Chassis Cleaner**

**14.1. UN number or ID number:** UN 1719  
**14.2. UN proper shipping name:** CAUSTIC ALKALI LIQUID, N.O.S. (SODIUM HYDROXIDE, SOLID)  
**14.3. Transport hazard class(es):** 8  
**14.4. Packing group:** III  
Hazard label: 8



Special Provisions: 223, 274  
Limited quantity: 5 L  
Excepted quantity: E1  
EmS: F-A, S-B

**Air transport (ICAO-TI/IATA-DGR)**

**14.1. UN number or ID number:** UN 1719  
**14.2. UN proper shipping name:** CAUSTIC ALKALI LIQUID, N.O.S. (SODIUM HYDROXIDE, SOLID)  
**14.3. Transport hazard class(es):** 8  
**14.4. Packing group:** III  
Hazard label: 8



Special Provisions: A3 A803  
Limited quantity Passenger: 1 L  
Passenger LQ: Y841  
Excepted quantity: E1  
IATA-packing instructions - Passenger: 852  
IATA-max. quantity - Passenger: 5 L  
IATA-packing instructions - Cargo: 856  
IATA-max. quantity - Cargo: 60 L

**14.5. Environmental hazards**

ENVIRONMENTALLY HAZARDOUS: No

**SECTION 15: Regulatory information****15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture****EU regulatory information**

Restrictions on use (REACH, annex XVII):

Entry 3, Entry 75

2010/75/EU (VOC): 0,04 % (0,424 g/l)





## RAPID Plus Engine & Chassis Cleaner

2004/42/EC (VOC): 0,04 % (0,424 g/l)  
Information according to 2012/18/EU (SEVESO III): Not subject to 2012/18/EU (SEVESO III)

### Additional information

To follow: 850/2004/EC, 79/117/EEC, 689/2008/EC  
Regulation (EC) No. 648/2004 [Detergents regulation]

### National regulatory information

Employment restrictions: Observe restrictions to employment for juveniles according to the 'juvenile work protection guideline' (94/33/EC).  
Water hazard class (D): 3 - highly hazardous to water

### Substance/product listed in the following inventories

EU / Schweiz	yes
Taiwan	unknown
New Zealand	yes
USA	yes
Canada	unknown
Australia	yes
Japan	yes
China	unknown
Korea	no
Philippines	yes

### 15.2. Chemical safety assessment

Chemical safety assessments for substances in this mixture were not carried out.

## SECTION 16: Other information

### Changes

This data sheet contains changes from the previous version in section(s): 6,7,9,15.

### Abbreviations and acronyms

ADR: Accord européen sur le transport des marchandises dangereuses par Route  
(European Agreement concerning the International Carriage of Dangerous Goods by Road)  
IMDG: International Maritime Code for Dangerous Goods  
IATA: International Air Transport Association  
GHS: Globally Harmonized System of Classification and Labelling of Chemicals  
EINECS: European Inventory of Existing Commercial Chemical Substances  
ELINCS: European List of Notified Chemical Substances  
CAS: Chemical Abstracts Service  
LC50: Lethal concentration, 50%



## RAPID Plus Engine & Chassis Cleaner

LD50: Lethal dose, 50%

### Classification for mixtures and used evaluation method according to GB CLP Regulation

Classification	Classification procedure
Skin Corr. 1; H314	On basis of test data
Eye Dam. 1; H318	Calculation method

### Relevant H and EUH statements (number and full text)

H290	May be corrosive to metals.
H302	Harmful if swallowed.
H314	Causes severe skin burns and eye damage.
H318	Causes serious eye damage.
H335	May cause respiratory irritation.
H412	Harmful to aquatic life with long lasting effects.

### Further Information

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)

© by SCHOLL Concepts GmbH